



MAXUS

Ambulance

- Spacious Area for Medical Treatment
- Professional Build for Medical Care
- Sufficient Devices for First Aid
- Efficient Functional Layout
- Type-A, Type-B, Type-C



BUILT FOR PROFESSIONALS

Emergency Use

V80 Ambulance is fitted with custom built fibreglass moulding panels, cabinets, and roof which offer a *Class 1- surface spread of flame protection*. The interior of the ambulance is shielded with a fire retardant insulation material for a better sound and heat protection.

Patient Transfer Vehicle

The use of fibreglass also makes cleaning easier from spills and stains. The floor board uses a PVC intergal foam board that is water proof, chemical proof, decay resistant and fire retardant. The floor is laminated with heavy duty anti-slip floor mat.

★ WESTSTAR



1. Overall layout. 3-seat bench, automatic loading stretcher
2. Medical care bench, first aid box, glass fiber reinforced partitions & stretcher
4. Glass fiber reinforced suspended ceiling, IV injection hook, exhaust fans
5. Built-in 230VAC & 12DC wall sockets
6. Integrated glass fiber reinforced interior system: touch system, oxygen collecting bar, humidification bottle and other specialized equipments

www.weststarmaxus.com

Weststar Maxus Sdn Bhd
 Main Office and Showroom:
 No.366, Jalan Tun Razak, 50400 Kuala Lumpur
 Tel : (+603) 2143 3331 | Fax : (+603) 2143 3332

Branches :
 No 27 Jalan Perintis UI/52 Seksyen UI Glenmarie 40150 Shah Alam Selangor / Tel:03-55679242
 No G34 Jalan Kolam 2 Taman Nong Chik 80200 Johor Bahru / Tel:07-2071333
 No 2118, Lot 2415, Lebuhr Darulaman,05150 Alor Star Kedah / Tel:04-7355785

This leaflet was printed in March 2017. Pictures and product information are only for your reference. Product specification should be subject to the real vehicle.

| V80 Ambulance Specification (Panel Van) | | | | |
|---|---------------------------------------|--|------------------|--------|
| Size | Length (mm) | 5700 | | |
| | Width (mm) | 1998 | | |
| | Height (mm) | 2552 (High Roof) | | |
| Wheelbase (mm) | | 3850 | | |
| G.V.W (Kg) | | 3500 | | |
| Maximum speed (km/h) | | 160 | | |
| Maximum passenger (persons) | | 4-7 | | |
| Tyre | | 215/75R16C | | |
| Fuel type | | Diesel | | |
| Power system | Type | 4 cylinder 2.5L CDI Diesel Twin Camshaft 16 Valve Turbo Intercooler Commonrail Injection Euro IV Green Engine Aluminium Cylinder Head with Cast Iron Black | | |
| | Displacement (ml) | 2499 | | |
| | Rated power (Ps/rpm) | 136/3800 | | |
| | Maximum torque (N-m/rpm) | 330/1800 | | |
| | Transmission | 5- Speed Manual (Front Wheel Drive) | | |
| | Fuel consumption (L/100km) | 6 (at 60km/h) | 9.4 (at 100km/h) | |
| Emission standard | Euro 4 | | | |
| Suspension | | Front : Independent McPherson Struts Rear : Transversal Leaf Spring | | |
| Brakes | | ABS + EBD+ BAS + 4 - Wheel Disc Brake | | |
| Wheels | | 16" Steel | | |
| Fitting and Equipment Specification | | | | |
| <ul style="list-style-type: none"> · Reverse sensor · Front and rear A/C blowers · PA Systems · Light bar strobe type with "AMBULANS" · 2 x LED flash light (front grill, left & right , roof & rear door) · 1 x 50W area light inside/rear ambulance · Rear windows tinted to 95% reduction | | | | |
| No | Type of Equipments | Type A | Type B | Type C |
| 1 | Emergency Medical & Trauma Kit (EMTS) | 1 Set | 1 Set | 1 Set |
| 2 | Oxygen Resuscitator | 1 | 1 | - |
| 3 | Portable Suction Machine | 1 | 1 | - |
| 4 | Automated External Defibrillator | 1 | 1 | - |
| 5 | Vital Sign Transport Monitor | 1 | 1 | - |
| 6 | Foldable Wheel Chair | 1 | 1 | 1 |
| 7 | Spinal Board | 1 | 1 | 1 |
| 8 | Scoop Stretcher | 1 | 1 | 1 |
| 9 | Immobilization Kit | 1 Set | 1 Set | - |
| 10 | Portable Automatic Ventilator | 1 | - | - |
| 11 | Paramedic Suite, Helmet, Safety Boot | 1 Set | - | - |
| 12 | Handheld Pulse Oxymeter | 1 | 1 | - |
| 13 | Glucometer | 1 | - | - |
| 14 | Triage Card | 100 | - | - |
| 15 | Dead Body Management Kit | 10 | - | - |
| 16 | Sharp Container | 1 Set | 1 Set | - |
| 17 | Primary Stretcher | 1 | 1 | 1 |
| 18 | Oxygen Tank | 2 | 2 | 2 |

This is for reference only. Actual configuration may vary. Configurations can be customized according to customer requirements.

Distributor